



PHGB 2100173 4-10-02  
USA *Priority Papers*  
INVESTOR IN PEOPLE

**CERTIFIED COPY OF  
PRIORITY DOCUMENT**

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 2006 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated

5 September 2001

*This Page Blank (uspto)*

**Request for grant of a patent**

(See notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
Gwent NP9 1RH

1.	Your reference	PHGB 010017	06FEB01 E603666-2 002879 F01/7700 0.00-0102882.8
2.	Patent application number (The Patent Office will fill in this part)	<b>0102882.8</b>	
3.	Full name, address and postcode of the or of each applicant ( <u>underline all surnames</u> )	KONINKLIJKE PHILIPS ELECTRONICS N.V. GROENEWOUDSEWEG 1 5621 BA EINDHOVEN THE NETHERLANDS 6 FEB 2001 7586605002 IS	
	Patents ADP Number (if you know it)		
	If the applicant is a corporate body, give the country/state of its incorporation	THE NETHERLANDS	
4.	Title of the invention	SIGNALLING SYSTEM AND A TRANSPONDER FOR USE IN THE SYSTEM	
5.	Name of your agent (if you have one)	KEVIN JAMES SCOTT	
	"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	Philips Corporate Intellectual Property Cross Oak Lane Redhill Surrey RH1 5HA	
	Patents ADP number (if you know it)	76889114001 IS	
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority Application number      Date of filing
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day/month/year)
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer "Yes" if:	YES	
	a) any applicant named in part 3 is not an inventor, or		
	b) there is an inventor who is not named as an applicant, or		
	c) any named applicant is a corporate body.		
	See note (d))		

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.  
Do not count copies of the same document.

Continuation sheets of this form

Description	7
Claims(s)	2
Abstract	1
Drawings	1 only

10. If you are also filing any of the following, state how many against each item:

Priority Documents

Translations of priority documents  
Statement of inventorship and right  
to grant of a patent (*Patents Form 7/77*)  
Request for preliminary examination and  
search (*Patents Form 9/77*)  
Request for substantive examination  
(*Patents Form 10/77*)  
Any other documents  
(*Please specify*)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

5<sup>th</sup> February 2001

12. Name and daytime telephone number of person to contact in the United Kingdom

01293 81 5281

K J SCOTT

**Warning**

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

**Notes**

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered "Yes" Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

## DESCRIPTION

**SIGNALLING SYSTEM AND A TRANSPONDER FOR USE  
IN THE SYSTEM**

5

The present invention relates to a signalling system which includes transponding devices for transmitting response signals in reply to interrogating signals transmitted by an interrogation station. The term transponding in the present specification is intended to include not only a response signal being  
10 derived, by example, dividing or multiplying the interrogating frequency but also a response signal which is generated independently of the interrogating frequency.

Many such systems exist which serve various functions, one of the most  
15 popularly known being shoplifting detector systems in which tags containing radio transponders are attached to higher value articles and interrogating stations, located beyond a pay point, detect those tags which have not been removed in the purchasing transaction. In more intelligent systems the tags are able to transmit digitally coded signals which can be used to identify the  
20 location of persons on say an offshore oil rig or can be used to identify cattle, for example cows, in an animal feeding system in which say the amount of feed is related to the volume of milk produced.

A simpler, less expensive system is the Philips I-CODE labelling system in which the transponders comprise inexpensive, self adhesive, smart passive  
25 labels which can be used in security applications, parcel distribution, baggage sorting and collection systems, retail sales and distribution, library services and source tagging (counterfeit protection).

Depending on the system architecture, the transponders may be passive which is generally understood to mean that batteries are not included  
30 in the tags and power is derived from the interrogating signal or other external excitation field either directly or through the use of current storage devices such as capacitors or they may be active which is generally understood to

mean that the tags include a battery, for example a lithium battery, for powering the transponding circuitry in the tag.

Although active tagging systems offer many performance advantages over their passive counterparts there are some circumstances when spurious,  
5 low levels of radiation from an active tag may be considered unacceptable. One case in point is the use of radio devices (either transmitters or active receivers) on board an aircraft. To be certain of meeting the strict regulations that govern these types of environment it may be necessary to implement an active tag with a true zero power standby mode. The problem with  
10 implementing this type of function is that it becomes rather difficult to re-activate the tag when the receiver has been placed into a completely disabled state because it cannot hear the "wake up" instruction.

EP-B1-0 299 557 discloses an identification system for stock farms in which an active transponder is connected to battery terminals only when the  
15 interrogation field has sufficient strength. For simple identification purposes such an arrangement is adequate and serves to extend the life of the battery.

However newer transponding signalling systems require the tag to be able to build-up a history of say the environment to which an article, such as a sealed parcel, has been subject during its handling, storage and transmission.  
20 This cannot be done if the transponding circuitry of an active tag is disabled by the battery being disconnected completely.

An object of the present invention is to eliminate or reduce significantly spurious radiation from the transponder circuitry of an active tag whilst allowing  
25 the tag to be activated when required.

According to one aspect of the present invention there is provided a signalling system comprising a transponder including a controller for controlling the operation of the transponder, a radio transceiver coupled to the controller by way of switching means, an electric current source coupled to the controller,  
30 and a radio signal receiving means coupled to the controller for providing signals for activating the switching means to inhibit or permit the operation of the radio transceiver, a transponder interrogation station for interrogating the

transponder by way of signals transmitted to, and received from, the radio transceiver, and a source of switching signals receivable by the signal receiving means when in range.

According to a second aspect of the present invention there is provided  
5 a transponder for use in an interrogation system, the transponder including a controller for controlling the operation of the transponder, a radio transceiver coupled to the controller by way of switching means, an electric current source coupled to the controller, and a radio signal receiving means coupled to the controller for providing signals for activating the switching means to inhibit or  
10 permit the operation of the radio transceiver.

The present invention is based on the realisation that certain functions of a tag can be energised even when spurious radiation from the tag is not permitted, but the transceiving section can be re-activated by way of a signal transmitted to a passive receiver which is coupled to the controller.

15 If it is desired to monitor the environmental changes to which an article carrying a tag has been subjected, transducers, such as temperature and humidity sensors, are provided and coupled to the controller which stores the data acquired in a RAM even when the transceiving section has been de-activated. Once the tag has been re-activated then on interrogation, the  
20 stored data can be read-out. The turning-off and -on of the transceiving section by the radio signal receiving means is done in a positive manner so that passing a de-activated tag through a normal interrogation field will not enable it to be reactivated. The characteristics of the interrogation signal may be completely different from the switching signal thereby reducing significantly  
25 the risk of inadvertent operation by an undesired signal.

The radio signal receiving means may comprise a passive radio receiver which derives its power from the switching signals.

An embodiment of a signalling system in accordance with the present  
30 invention will now be described, by way of example, with reference to the single figure of the accompanying drawing.

The illustrated embodiment comprises three main components a transponder tag 10, an interrogation station 12 and a switching signal station 14. Although a single tag 10 has been shown, in reality there will be a large plurality of tags in use.

5       The transponder tag 10 comprises a microcontroller 20 having connections to various off-chip devices. The microcontroller 20 and the off-chip devices are powered by a battery 22, for example a lithium cell. An EEPROM 24 stores the software and identification coding necessary for the operation of the microcontroller 20. A number of sensors or transducers 26,  
10   28, 30 for monitoring the environment and handling of an article to which the tag 10 is attached are connected to the microcontroller 20. The sensors may include a temperature sensor 26, a humidity sensor 28 and anything else, for example an accelerometer to monitor heavy handling and/or dropping of the article. The data from these sensors is digitised by the microcontroller 20 and  
15   stored in a random access memory (RAM) 32.

A transceiver 34 is coupled to the microcontroller 20 by way of an electronic switch 36 controlled by the microcontroller 20. The transceiver 34 operates at a frequency of 868 MHz and receives interrogating signals from, and sends response signals to, the interrogation station 12. The interrogating  
20   signals may include an identification code and/or the response signals may be encoded. The illustrated system operates at a single frequency which has the advantage that the transceiver 34 can lock its frequency to that of the interrogating signal. However the transceiver 34 could transmit on a frequency derived from the interrogating signal, for example a harmonic or sub-harmonic,  
25   or transmit on a frequency unrelated to that of the interrogating signal.

A simple passive radio receiver 38, which may comprise a spiral antenna 40, is coupled to the microcontroller 20. The receiver 38 provides control signals relayed from the switching signal station 14, which signals are used by the microcontroller 20 for actuating the electronic switch 36. The  
30   switching signal station 14 operates at a frequency which is significantly different from that of the interrogating signal, for example 13.56 MHz. If desired the signals may be encoded using the Philips I-CODE which is a code



used widely with passive tags. If so, an I-CODE chip 42 manufactured by Philips Semiconductors is coupled in the signal path between the antenna 40 and the microcontroller 20. Optionally the receiver 38 may comprise a transceiver which enables signals to be transmitted to the switching signal station 14 by way of the antenna 40.

The interrogation station 12 comprises a transceiver 50 which is coupled to a processor 52 which operates in accordance with software stored in an EEPROM 24. A large RAM 56 arranged as a plurality of storage areas A1 to An, B1 to Bn and C1 to Cn store environmental data relayed from respective transponder tags 10 for later recovery. A modem 58 interfaces the processor 52 with data links generally represented by the block 60.

In normal operation the transponder tag 10 is attached to an article, for example a parcel, to be shipped by a courier over an air link. Details of the addressee are stored together with the tag's own identity in the EEPROM 24. In the handling of the parcel it passes through a succession of interrogation stations 12. At each station the identity and destination are noted and used to facilitate the handling and routing of the article. Also any data sensed by the sensors 26, 28, 30 and stored in the RAM 32 is read-out in response to a request from the interrogation station and relayed by the transceiver 34 to the station 12 where it is stored at one of the plurality of storage areas A1 to An, B1 to Bn, C1 to Cn of the RAM 56. The reading-out of the data from the RAM 32 may be done destructively or alternatively the stored data may be overwritten by new data after it has been read-out and relayed to the interrogation station.

At an air freight terminal the article after being sorted is subject to a "switch-off" signal transmitted by a switching station 14 which causes the microcontroller to open the switch 36 disabling the transceiver 34 whilst leaving the remainder of the tag 10 active but not producing radiation of any significance. In this state the microcontroller 20 can still ensure that environmental data detected by the sensors 26, 28, 30 can be stored in the RAM 32 but is unable to respond to any interrogation signals from a station 12.

The article can then be loaded onto an aircraft in the sure knowledge that the transceiver 34 has been muted.

At the destination air freight terminal the article is passed by a switching signal station 14 which transmits a "switch-on" signal which is detected by the passive receiver 38. The microcontroller 20 generates a signal closing the switch 36 thereby enabling the transceiver 34. Thereafter the tag 10 is able to respond to interrogating signals and to transfer any data stored in the RAM 32.

If desired data relating to a particular tag and stored at a number of interrogation stations 12 can be collated by one station in readiness to be read-out if a query arises over the environmental conditions to which the article had been exposed.

If the passive radio receiver 38 is adapted to transmit signals, such as I-CODE signals, it will be possible to extend the versatility of the tag 10 by enabling it to be woken-up to transmit its identity and then return to a sleep mode. Such a capability will enable parcels having a tag to be sorted as they are transported along conveyor belts and guided by deflectors into the appropriate bins. The final destination address can be stored at the switching station 14 and this information is used to actuate the deflectors.

In the present specification and claims the word "a" or "an" preceding an element does not exclude the presence of a plurality of such elements. Further, the word "comprising" does not exclude the presence of other elements or steps than those listed.

From reading the present disclosure, other modifications will be apparent to persons skilled in the art. Such modifications may involve other features which are already known in the design, manufacture and use of transponding systems and component parts therefor and which may be used instead of or in addition to features already described herein. Although claims have been formulated in this application to particular combinations of features, it should be understood that the scope of the disclosure of the present application also includes any novel feature or any novel combination of features disclosed herein either explicitly or implicitly or any generalisation thereof, whether or not it relates to the same invention as presently claimed in

any claim and whether or not it mitigates any or all of the same technical problems as does the present invention. The applicants hereby give notice that new claims may be formulated to such features and/or combinations of such features during the prosecution of the present application or of any  
5 further application derived therefrom.

## CLAIMS

1. A signalling system comprising a transponder including a controller for controlling the operation of the transponder, a radio transceiver coupled to the controller by way of switching means, an electric current source coupled to the controller, and a radio signal receiving means coupled to the controller for providing signals for activating the switching means to inhibit or permit the operation of the radio transceiver, a transponder interrogation station for interrogating the transponder by way of signals transmitted to, and received from, the radio transceiver, and a source of switching signals receivable by the signal receiving means when in range.

2. A system as claimed in claim 1, characterised in that the transponder further comprises at least one transducer coupled to the controller and a random access memory for storing data representative of information produced by the transponder.

3. A system as claimed in claim 2, characterised in that the transponder interrogation station has storage means for storing said data relayed by the transponder in response to an interrogation signal.

4. A system as claimed in claim 1, 2 or 3, characterised in that the radio receiving means comprises a passive radio receiver and in that the source of switching signals comprises a radio transmitter for communicating with the passive radio receiver.

5. A system as claimed in any one of claims 1 to 4, characterised in that the transponder interrogation station and the source of switching signals operate at different frequencies.

30

6. A transponder for use in an interrogation system, the transponder including a controller for controlling the operation of the transponder, a radio

transceiver coupled to the controller by way of switching means, an electric current source coupled to the controller, and a radio signal receiving means coupled to the controller for providing signals for activating the switching means to inhibit or permit the operation of the radio transceiver.

5

7. A transponder as claimed in claim 6, characterised in that the transponder further comprises at least one transducer coupled to the controller and a random access memory for storing data representative of information produced by the transponder.

10

8. A transponder as claimed in claim 7, characterised in that the transponder interrogation station has storage means for storing said data relayed by the transponder in response to an interrogation signal.

15

9. A transponder as claim 6, 7 or 8, characterised in that the radio receiving means comprises a passive radio receiver.

20

10. A signalling system constructed and arranged to operate substantially as hereinbefore described with reference to and as shown in the accompanying drawing.

11. A transponder constructed and arranged to operate substantially as hereinbefore described with reference to and as shown in the accompanying drawing.

## ABSTRACT



**SIGNALLING SYSTEM AND A TRANSPONDER FOR USE IN  
THE SYSTEM**

5

A signalling system includes a plurality of active transponders (10), an interrogation station (12) and a source (14) of switching signals. Each of the transponders has a microcontroller (20), a radio transceiver (34) for responding to radio interrogation signals from the interrogation station, the  
10 radio transceiver being coupled to the controller by way of switching means (36) which switches the transceiver on or off whilst leaving the microcontroller active, and a passive receiver (38) for receiving switching signals from the source of switching signals which signals are used by the microcontroller for switching-on or -off the transceiver. Transducers (26, 28, 30) may be coupled  
15 to the microcontroller for monitoring environmental features, such as ambient temperature and humidity, and data relating to the features is stored in a RAM (32) in readiness to be relayed to storage means (56) in the interrogation station (12) as and when required. Signals received by the passive receiver enable the radio transceiver to be de-activated in locations, such as in an  
20 aircraft, where spurious radiation from the transponder is not permitted and to be re-activated when removed from such a location.

(Single Figure)

1/1



***This Page Blank (uspto)***